Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/NL04/000855

International filing date: 09 December 2004 (09.12.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US

Number: 60/608,938

Filing date: 09 December 2003 (09.12.2003)

Date of receipt at the International Bureau: 23 May 2005 (23.05.2005)

Remark: Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)



0 9. 04.05

PA 1301560

ANTORUNTURED SYMMUNES OF WORK CAN

TO ATH TO WHOM THUSE; PRESERTS; SHAVE, COME;

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

April 11, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/608,938

FILING DATE: December 09, 2003

By Authority of the

COMMISSIONER OF PATENTS AND TRADEMARKS

P. SWAIN

Certifying Officer

Us the

PATENT APPLICATION SERIAL NO.	PATENT	APPLICATION	SERIAL NO	
-------------------------------	--------	-------------	-----------	--

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE FEE RECORD SHEET

| Stment date: 11/29/2004 | UEDUVIJE | 1/2004 | HVUONG1 | 00000101 | 033975 | 10730255 | 121005 | 160.00 CR | C:1807 | 50.00 CR |

9/2004 UEDUVIJE 0000D013 033975 60608938

C:1005 160.00 DA C:1052 50.00 DA

PTO-1556 (5/87)

*U.S. GPO: 2000-468-987/39595 *

Atty Dkt: 081468/307119 Client Ref.: P-1755.000-US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

e PATENT APPLICATION of: FRITS JURGEN VAN HOUT et al.

Application No.: 10/730,255

Confirmation No.: 3342

Filed: December 9, 2003

Group Art Unit: 2881

For: SENSOR FOR LITHOGRAPHIC APPARATUS AND METHOD OF OBTAINING

MEASUREMENTS OF LITHOGRAPHIC APPARATUS

PETITION TO CONVERT THE ABOVE-CAPTIONED NON-PROVISIONAL PATENT APPLICATION TO A PROVISIONAL PATENT APPLICATION UNDER 37 C.F.R. § 1.53(c) AND AMENDMENT

Box DAC Assistant Commissioner for Patents Washington, DC 20231

Dear Sir:

This petition is filed in response to the Notice to File Missing Parts mailed March 9, 2004.

Pursuant to 37 C.F.R. § 1.53(c), Applicants respectfully request that the above-captioned non-provisional patent application be converted to a provisional patent application. The fee of \$130.00 required for this Petition under 37 C.F.R. § 1.17(h) accompanies this request together with the \$160.00 filing fee required by 37 C.F.R. § 1.16(k). (See also M.P.E.P. § 610.01(c).)

The above-entitled patent application has not been abandoned, the issue fee has not been paid, and more than twelve months have not expired since the filing of the non-provisional application. Accordingly, Applicants believe that this request is proper.

Since Applicants make this petition before payment of the filing fee required by the Notice to File Missing Parts dated March 9, 2004, Applicants respectfully submit that the regular filing fee is not required, only the \$160.00 filing fee for a provisional application under 37 C.F.R. § 1.16(k).

9/21/2004 HVUUNG1 00000101 033975 10730255

1 FC:1005

160.00 DA 50.00 DA

30480078v1



United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandra, Vignisa 22313-1450 /Jajinia 22313-1450

APPLICATION NUMBER

FILING OR 371(c) DATE

FIRST NAMED APPLICANT

ATTY, DOCKET NO.

10/730,255

12/09/2003

Frits Jurgen Van Hout

081468-0307119

CONFIRMATION NO.

OC00000014627805

00909 PILLSBURY WINTHROP, LLP P.O. BOX 10500 MCLEAN, VA 22102

Date Mailed: 11/30/2004

DECISION GRANTING REQUEST TO CONVERT TO PROVISIONAL

This is a decision on the request under 37 CFR 1.53(c)(2) received in the U.S. Patent and Trademark Office on 09/17/2004, to convert the above-identified application to a provisional application under 35 U.S.C. 111(b) and 37 CFR 1.53(c).

The request is granted.

The application will be processed in the Office of Initial Patent Examination (OIPE) as a provisional application under 35 U.S.C. 111(b) and 37 CFR 1.53(c), including the assignment of a new provisional application number.

The provisional application number is 60/608,938. The filing receipt for the provisional application number will be mailed to the applicant by OIPE in due course.

JOHN S DILL

Office of Initial Patent Examination

(703) 308-0910

PART 2'- OFFICE COPY

PTO/SB/05 (06-03)
Approved for use through 07/31/2003, OMB 0651-0032

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.							
UTILITY	Attorney Docket No.	081468-0307119					
PATENT APPLICATION	First Inventor	VAN HOUT ET AL.					
TRANSMITTAL	Tille	Sensor for Lithographic Apparatus an	d				
(Only for new nonprovisional applications under 37 CFR 1.63(b))	Express Mail Label No.						
APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO:	Mell Stop Patent Application Commissioner for Patents P.O. Box 1450 Aloxandria VA 22313-1450	ρ				
1. Fee Transmittal Form (e.g., PTO/SB/17) (Submil an original and a duplicate for fee processing) Applicant claims small entity status. See 37 CFR 1.27. 3. X Specification [Total Pages 24] (preferred arrangement ast forth below) - Descriptive little of the Invention - Cross Reference to Related Applications - Statement Regarding Fed sponsored R & D - Reference to sequence listing, a table, or a computer program listing appendix - Background of the Invention - Brief Summany of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure 4. X Drawing(s) (35 U.S.C. 113) [Total Sheets 2] 5. Oath or Declaration [Total Sheets] a. Newly executed (original or copy) b. Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 18 completed) i. DELETIONOF INVENTOR(S) Signed statement attached deteiting inventor(s) name in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b). 6. X Application Data Sheet. See 37 CFR 1.76	8. Nucleotide and/or A (if applicable, all ne a.	O-R in duplicate, large table or tram (Appendix) mino Acid Sequence Submission cessary) r Reader Form (CRF) ition Sequence Listing on: ROM or CD-R (2 coples); or the copies of the copi	5 				
18. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in the first sentence of the specification following the title, or in an Application Data Sheet under 37 CFR 1.76:							
Continuation Divisional Continuation-in-part (CIP) of prior application No.: Art Unit: For CONTINUATION OF DIVISIONAL APPS only; The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.							
	NDENCE ADDRESS	7					
	OR L	Correspondence address below					
Name							
Address	Colota I	70. 0-1.					
City Country	State	Zip Code					
Name (PrintlType) Kerry T. Hartman A	Registration No. (Attorne						
Signature Rerry 1. Hartman	Two-sending no. Manite	Date 12/09/0	03				

Registration No. (Attorney/Agenti) 41818

Signature

Registration No. (Attorney/Agenti) 41818

Date 12/09/03

This collection of information is required by 37 CFR 1.53(b). The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Operatment of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Patient Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

PATENT

Attorney Docket No. 081468-0307119 Client Reference: P-1755.000-US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

VAN HOUT, Frits Jurgen

VAN BOMMEL, Josephus Antonius Maria

DIRKSEN, Peter KROON, Mark and

JUFFERMANS, Casparus Anthonius Henricus

Application No.:

TO BE ASSIGNED

Confirmation

No:

Filed:

December 9, 2003

Group No.: Examiner

For:

SENSOR FOR LITHOGRAPHIC APPARATUS AND METHOD OF OBTAINING

MEASUREMENTS OF LITHOGRAPHIC APPARATUS

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

APPLICATION DATA SHEET 37 C.F.R. § 1.76

BIBLIOGRAPHIC DATA

1. Applicant information

First applicant: Frits Jurgen VAN HOUT

Citizenship: The Netherlands

Residence: Hofstraat 41, Retie 2470, Belgium

Second applicant: Josephus Antonius Maria VAN BOMMEL

Citizenship: The Netherlands

Residence: Krommeweg 1, NL-5271 CV Sint Michielsgestel, The Netherlands

Third applicant: Peter DIRKSEN Citizenship: The Netherlands

Residence: Berkenstraat 6, NL-5553 EK Valkenswaard, The Netherlands

Fourth applicant: Mark KROON Citizenship: The Netherlands

Residence: Groeneweg 49, NL-3531 VB Utrecht, The Netherlands

Fifth applicant: Casparus Anthonius Henricus JUFFERMANS

Citizenship: The Netherlands

Residence: Slechtvalk 6, NL-5554 BM Valkenswaard, The Netherlands

Application Date Sheet--page 1 of 2

© 2002 Matthew Bender & Company, Inc., a member of the LexisNexis Group.

2. Correspondence information

Correspondence for this application should be addressed as follows:

Customer No.: 00909

3. Application information

Title of Invention: SENSOR FOR LITHOGRAPHIC APPARATUS AND METHOD

OF OBTAINING MEASUREMENTS OF LITHOGRAPHIC APPARATUS

Docket number assigned to this application: 081468-0307119

Suggested Classification:

Class:

Subclass:

Technology Center to which subject matter is assigned:

Total number of drawing sheets: 2

Type of application:

Utility

Application is to be published. Suggested drawing figure for publication: FIGURE 2

Secrecy order under § 5.2:

This application does not disclose subject matter of an application which is under a secrecy order pursuant to § 5.2.

4. Representative information

The following have a power of attorney or authorization of agent in this application:

Customer No.: 00909

5. Assignee information

The assignee(s) of this application is/are:

ASML NETHERLANDS B.V.

De Run 1110, NL-5503 LA Veldhoven, The Netherlands

Extent of interest of assignee in application: ENTIRE RIGHT, TITLE AND INTEREST

Date: December 9, 2003

Signature of Practitioner

Kerry T. Hartman PILLSBURY WINTHROP LLP Reg. No.: 41818

P.O. Box 10500 McLean, VA 22102

Tel. No.: (703) 905-2085

Customer No.: 00909

Application Date Sheet--page 2 of 2

© 2002 Matthew Bender & Company, Inc., a member of the LexisNexis Group.

Al	PPLICATION	UNDER UNITE	DSTAI	ES PATENT LAWS
Atty. Dkt. No.	307119			
Invention:		ITHOGRAPHIC APPAR 'S OF LITHOGRAPHIC		METHOD OF OBTAINING JS
Inventor (s):	DIRKSEN, Peter KROON, Mark	: Jurgen Josephus Antonius Maria Casparus Anthonius Her		
				Address communications to the correspondence address associated with our Custom r No 00909 Pillsbury Winthrop LLP
/				
			,	
				This is a:
				Provisional Application
		•	\boxtimes	Regular Utility Application
				Continuing Application The contents of the parent are incorporated by reference
4				PCT National Phase Application
				Design Application
				Reissue Application
				Plant Application
				Substitute Specification Sub. Spec Filed in App. No. /
			. 🗆	Marked up Specification re Sub. Spec. filed/

SPECIFICATION

30420176_1.DOC

PAT-100CN 8/03

SENSOR FOR LITHOGRAPHIC APPARATUS AND METHOD OF OBTAINING MEASUREMENTS OF LITHOGRAPHIC APPARATUS

FIELD OF THE INVENTION

[0001] The present invention relates to lithographic projection apparatus and methods.

BACKGROUND

[0002] The term "patterning structure" as here employed should be broadly interpreted as referring to any structure or field that may be used to endow an incoming radiation beam with a patterned cross-section, corresponding to a pattern that is to be created in a target portion of a substrate; the term "light valve" can also be used in this context. It should be appreciated that the pattern "displayed" on the patterning structure may differ substantially from the pattern eventually transferred to e.g. a substrate or layer thereof (e.g. where pre-biasing of features, optical proximity correction features, phase and/or polarization variation techniques, and/or multiple exposure techniques are used). Generally, such a pattern will correspond to a particular functional layer in a device being created in the target portion, such as an integrated circuit or other device (see below). A patterning structure may be reflective and/or transmissive. Examples of patterning structure include:

[0003] - A mask. The concept of a mask is well known in lithography, and it includes mask types such as binary, alternating phase-shift, and attenuated phase-shift, as well as various hybrid mask types. Placement of such a mask in the radiation beam causes selective transmission (in the case of a transmissive mask) or reflection (in the case of a reflective mask) of the radiation impinging on the mask, according to the pattern on the mask. In the case of a mask, the support structure will generally be a mask table, which ensures that the mask can be held at a desired position in the incoming radiation beam, and that it can be moved relative to the beam if so desired.

- A programmable mirror array. One example of such a device is a matrixaddressable surface having a viscoelastic control layer and a reflective surface. The basic principle behind such an apparatus is that (for example) addressed areas of the reflective surface reflect incident light as diffracted light, whereas unaddressed areas reflect incident light as undiffracted light. Using an appropriate filter, the undiffracted light can be filtered out of the reflected beam, leaving only the diffracted light behind; in this manner, the beam becomes patterned according to the addressing pattern of the matrix-addressable surface. An array of grating light valves (GLVs) may also be used in a corresponding manner, where each GLV may include a plurality of reflective ribbons that can be deformed relative to one another (e.g. by application of an electric potential) to form a grating that reflects incident light as diffracted light. A further alternative embodiment of a programmable mirror array employs a matrix arrangement of very small (possibly microscopic) mirrors, each of which can be individually tilted about an axis by applying a suitable localized electric field, or by employing piezoelectric actuation means. For example, the mirrors may be matrixaddressable, such that addressed mirrors will reflect an incoming radiation beam in a different direction to unaddressed mirrors; in this manner, the reflected beam is patterned according to the addressing pattern of the matrix-addressable mirrors. The required matrix addressing can be performed using suitable electronic means. In both of the situations described hereabove, the patterning structure can comprise one or more programmable mirror arrays. More information on mirror arrays as here referred to can be gleaned, for example, from United States Patents No. 5,296,891 and No. 5,523,193 and PCT patent applications WO 98/38597 and WO 98/33096, which documents are incorporated herein by reference. In the case of a programmable mirror array, the support structure may be embodied as a frame or table, for example, which may be fixed or movable as required.

[0005] - A programmable LCD panel. An example of such a construction is given in United States Patent No. 5,229,872, which is incorporated herein by reference. As above, the support structure in this case may be embodied as a frame or table, for example, which may be fixed or movable as required.

[0006] A lithographic apparatus may include a support structure that supports (i.e. bears the weight of) the patterning structure. The support structure may hold the

patterning structure in a particular fashion that depends on such factors as the orientation of the patterning structure, the design of the lithographic apparatus, and other conditions such as, for example, whether or not the patterning means is held in a vacuum environment. The support may include mechanical clamping, vacuum, or other clamping techniques (for example, electrostatic clamping, possibly under vacuum conditions). The support structure may be a frame or a table, for example, which may be fixed or movable as required and which may ensure that the patterning means is at a desired position, for example with respect to the projection system.

[0007] Any use of the terms "reticle" or "mask" herein may be considered synonymous with the more general term "patterning structure." For purposes of simplicity, the rest of this text may, at certain locations, specifically direct itself to examples involving a mask (or "reticle") and mask table (or "reticle table"); however, the general principles discussed in such instances should be seen in the broader context of the patterning structure as hereabove set forth.

[0008] A lithographic apparatus may be used to apply a desired pattern onto a surface (e.g. a target portion of a substrate). Lithographic projection apparatus can be used, for example, in the manufacture of integrated circuits (ICs). In such a case, the patterning structure may generate a circuit pattern corresponding to an individual layer of the IC, and this pattern can be imaged onto a target portion (e.g. comprising one or more dies and/or portion(s) thereof) on a substrate (e.g. a wafer of silicon or other semiconductor material) that has been coated with a layer of radiation-sensitive material (e.g. resist). In general, a single wafer will contain a whole matrix or network of adjacent target portions that are successively irradiated via the projection system (e.g. one at a time).

[0009] Among current apparatus that employ patterning by a mask on a mask table, a distinction can be made between two different types of machine. In one type of lithographic projection apparatus, each target portion is irradiated by exposing the entire mask pattern onto the target portion at once; such an apparatus is commonly referred to as a wafer stepper. In an alternative apparatus — commonly referred to as a step-and-scan apparatus — each target portion is irradiated by progressively scanning the mask pattern under the projection beam in a given reference direction

(the "scanning" direction) while synchronously scanning the substrate table parallel or anti-parallel to this direction; since, in general, the projection system will have a magnification factor M (generally < 1), the speed V at which the substrate table is scanned will be a factor M times that at which the mask table is scanned. A projection beam in a scanning type of apparatus may have the form of a slit with a slit width in the scanning direction. More information with regard to lithographic devices as here described can be gleaned, for example, from United States Patent No. 6,046,792, which is incorporated herein by reference.

[00010] In a manufacturing process using a lithographic projection apparatus, a pattern (e.g. in a mask) is imaged onto a substrate that is at least partially covered by a layer of radiation-sensitive material (e.g. resist). Prior to this imaging procedure, the substrate may undergo various other procedures such as priming, resist coating, and/or a soft bake. After exposure, the substrate may be subjected to other procedures such as a post-exposure bake (PEB), development, a hard bake, and/or measurement/inspection of the imaged features. This set of procedures may be used as a basis to pattern an individual layer of a device (e.g. an IC). For example, these transfer procedures may result in a patterned layer of resist on the substrate. One or more pattern processes may follow, such as deposition, etching, ion-implantation (doping), metallization, oxidation, chemo-mechanical polishing, etc., all of which may be intended to create, modify, or finish an individual layer. If several layers are required, then the whole procedure, or a variant thereof, may be repeated for each new layer. Eventually, an array of devices will be present on the substrate (wafer). These devices are then separated from one another by a technique such as dicing or sawing, whence the individual devices can be mounted on a carrier, connected to pins, etc. Further information regarding such processes can be obtained, for example, from the book "Microchip Fabrication: A Practical Guide to Semiconductor Processing," Third Edition, by Peter van Zant, McGraw Hill Publishing Co., 1997, ISBN 0-07-067250-4.

[00011] A substrate as referred to herein may be processed before or after exposure: for example, in a track (a tool that typically applies a layer of resist to a substrate and develops the exposed resist) or a metrology or inspection tool. Where applicable, the disclosure herein may be applied to such and other substrate processing tools. Further, the substrate may be processed more than once (for example, in order to

create a multi-layer IC), so that the term substrate as used herein may also refer to a substrate that already contains multiple processed layers.

[00012] The term "projection system" should be broadly interpreted as encompassing various types of projection system, including refractive optics, reflective optics, and catadioptric systems, for example. A particular projection system may be selected based on factors such as a type of exposure radiation used, any immersion fluid(s) or gas-filled areas in the exposure path, whether a vacuum is used in all or part of the exposure path, etc. For the sake of simplicity, the projection system may hereinafter be referred to as the "lens." The radiation or illumination system may also include components operating according to any of these design types for directing, shaping, reducing, enlarging, patterning, and/or otherwise controlling the projection beam of radiation, and such components may also be referred to below, collectively or singularly, as a "lens."

[00013] Further, the lithographic apparatus may be of a type having two or more substrate tables (and/or two or more mask tables). In such "multiple stage" devices the additional tables may be used in parallel, or preparatory steps may be carried out on one or more tables while one or more other tables are being used for exposures. Dual stage lithographic apparatus are described, for example, in U.S. Patent No. 5,969,441 and PCT Application No. WO 98/40791, which documents are incorporated herein by reference.

[00014] The lithographic apparatus may also be of a type wherein the substrate is immersed in a liquid having a relatively high refractive index (e.g. water) so as to fill a space between the final element of the projection system and the substrate. Immersion liquids may also be applied to other spaces in the lithographic apparatus, for example, between the mask and the first element of the projection system. The use of immersion techniques to increase the effective numerical aperture of projection systems is well known in the art.

[00015] In the present document, the terms "radiation" and "beam" are used to encompass all types of electromagnetic radiation, including ultraviolet radiation (e.g. with a wavelength of 365, 248, 193, 157 or 126 nm) and EUV (extreme ultra-violet

radiation, e.g. having a wavelength in the range 5-20 nm), as well as particle beams (such as ion or electron beams).

[00016] Although specific reference may be made in this text to the use of lithographic apparatus in the manufacture of ICs, it should be explicitly understood that such an apparatus has many other possible applications. For example, it may be employed in the manufacture of integrated optical systems, guidance and detection patterns for magnetic domain memories, liquid-crystal display panels, thin-film magnetic heads, DNA analysis devices, etc. The skilled artisan will appreciate that, in the context of such alternative applications, any use of the terms "wafer" or "die" in this text should be considered as being replaced by the more general terms "substrate" and "target portion", respectively.

[00017] The optical properties of the optical components of a lithographic apparatus may vary during operation. To maintain a predetermined level of quality, it may be important to know whether any anomalies in the optical system of the lithographic apparatus are present. The optical properties can be tested using special-purpose test equipment, e.g. as described in U.S. Published Patent Application No. US2002/0001088A. This publication describes an apparatus for wave front detection, which may be used e.g. to measure and correct aberration in the optical components of a stepper or scanner for microlithography.

[00018] These known test devices are positioned in the position of a wafer being exposed, requiring disassembly of the lithography apparatus to a large extent. As a consequence, the apparatus to be tested may have to be taken out of operation for a considerable amount of time.

SUMMARY

[00019] A sensor arrangement according to one embodiment of the invention comprises a substrate having the following: at least one sensor element; a processing circuit connected to the at least one sensor element; an input/output interface connected to the processing circuit; and a power supply unit configured to supply

operating power to at least one other component of the sensor arrangement. The at least one sensor element is provided as an integrated circuit in the substrate.

Apparatus including such arrangements, and methods of using such arrangements, are also disclosed.

BRIEF DESCRIPTION OF THE DRAWINGS

[00020] Embodiments of the invention will now be described, by way of example only, with reference to the accompanying schematic drawings in which:

[00021] Figure 1 depicts a lithographic apparatus in conjunction with which an embodiment of the current invention can be employed.

[00022] Figure 2 depicts a sensor arrangement according to an embodiment of the invention.

[00023] Figure 3 depicts a simplified view of a dedicated test mask in combination with a sensor arrangement according to an embodiment of the invention.

[00024] In the Figures, corresponding reference symbols indicate corresponding parts.

DETAILED DESCRIPTION

[00025] Embodiments of the invention include, for example, a sensor arrangement that may be used to allow testing of the optical components of an apparatus without requiring a major effort to prepare and perform the testing. Such a sensor arrangement may be used to measure properties, such as optical properties, of a device arranged to process substrates (such as a lithographic apparatus).

[00026] Figure 1 schematically depicts a lithographic projection apparatus in conjunction with which an embodiment of the current invention can be employed. The apparatus comprises:

[00027] A radiation system configured to supply (e.g. having structure capable of supplying) a projection beam of radiation. In this particular example, the radiation system for supplying a projection beam PB of radiation (e.g. UV or EUV radiation) comprises a radiation source SO and an illuminator IL;

[00028] A support structure configured to support a patterning structure capable of patterning the projection beam. In this example, a first object table (mask table) MT is provided with a mask holder for holding a mask MA (e.g. a reticle), and is connected to a first positioning structure for accurately positioning the mask with respect to item PL;

[00029] A second object table (substrate table) configured to hold a substrate. In this example, substrate table WT is provided with a substrate holder for holding a substrate W (e.g. a resist-coated semiconductor wafer), and is connected to a second positioning structure for accurately positioning the substrate with respect to item PL and (e.g. interferometric) measurement structure IF, which is configured to accurately indicate the position of the substrate and/or substrate table with respect to lens PL; and

[00030] A projection system ("lens") configured to project the patterned beam. In this example, projection system PL (e.g. a refractive lens group, a catadioptric or catoptric system, and/or a mirror system) is configured to image an irradiated portion of the mask MA onto a target portion C (e.g. comprising one or more dies and/or portion(s) thereof) of the substrate W. Alternatively, the projection system may project images of secondary sources for which the elements of a programmable patterning structure may act as shutters. The projection system may also include a microlens array (MLA), e.g. to form the secondary sources and to project microspots onto the substrate.

[00031] As here depicted, the apparatus is of a transmissive type (e.g. has a transmissive mask). However, in general, it may also be of a reflective type, for example (e.g. with a reflective mask). Alternatively, the apparatus may employ another kind of patterning structure, such as a programmable mirror array of a type as referred to above.

[00032] The source SO (e.g. a mercury lamp, an excimer laser, an electron gun, a laser-produced plasma source or discharge plasma source, or an undulator provided around the path of an electron beam in a storage ring or synchrotron) produces a beam of radiation. This beam is fed into an illumination system (illuminator) IL, either directly or after having traversed a conditioning structure or field, such as a beam expander Ex, for example. The illuminator IL may comprise an adjusting structure or field AM for setting the outer and/or inner radial extent (commonly referred to as σ-outer and σ-inner, respectively) of the intensity distribution in the beam, which may affect the angular distribution of the radiation energy delivered by the projection beam at, for example, the substrate. In addition, the apparatus will generally comprise various other components, such as an integrator IN and a condenser CO. In this way, the beam PB impinging on the mask MA has a desired uniformity and intensity distribution in its cross-section.

[00033] It should be noted with regard to Figure 1 that the source LA may be within the housing of the lithographic projection apparatus (as is often the case when the source LA is a mercury lamp, for example), but that it may also be remote from the lithographic projection apparatus, the radiation beam which it produces being led into the apparatus (e.g. with the aid of a beam delivery system BD comprising, for example, suitable direction mirrors and/or a beam expander); this latter scenario is often the case when the source LA is an excimer laser. The current invention and claims encompass both of these scenarios. The source SO and the illuminator IL, together with the beam delivery system BD if any, may be referred to as a radiation system.

[00034] The beam PB subsequently intercepts the mask MA, which is held on a mask table MT. Having traversed (alternatively, having been selectively reflected by) the mask MA, the beam PB passes through the lens PL, which focuses the beam PB onto a target portion C of the substrate W. With the aid of the second positioning structure PW (and interferometric measuring structure IF), the substrate table WT can be moved accurately, e.g. so as to position different target portions C in the path of the beam PB. Similarly, the first positioning structure PM (possibly in conjunction with another position sensor, not explicitly shown) can be used to accurately position the mask MA with respect to the path of the beam PB, e.g. after mechanical retrieval of

the mask MA from a mask library, or during a scan. In general, movement of the object tables MT, WT will be realized with the aid of a long-stroke module (coarse positioning) and a short-stroke module (fine positioning), which are not explicitly depicted in Figure 1. However, in the case of a wafer stepper (as opposed to a step-and-scan apparatus) the mask table MT may just be connected to a short stroke actuator, or may be fixed. Mask MA and substrate W may be aligned using mask alignment marks M1, M2 and substrate alignment marks P1, P2.

[00035] The depicted apparatus can be used in several different modes:

[00036] 1. In step mode, the mask table MT is kept essentially stationary, and an entire mask image is projected at once (i.e. in a single "flash") onto a target portion C. The substrate table WT is then shifted in the x and/or y directions so that a different target portion C can be irradiated by the beam PB. In step mode, the maximum size of the exposure field may limit the size of a target portion C imaged in a single static exposure;

[00037] 2. In scan mode, essentially the same scenario applies, except that a given target portion C is not exposed in a single "flash". Instead, the mask table MT is movable in a given direction (the so-called "scan direction", e.g. the y direction) with a speed v, so that the projection beam PB is caused to scan over a mask image. Concurrently, the substrate table WT is simultaneously moved in the same or opposite direction at a speed V = Mv, in which M is the magnification of the lens PL (typically, M = ¼ or 1/5). The velocity and direction of the substrate table WT relative to the mask table MT may determined by the magnification (or demagnification) and image reversal characteristics of the projection system PL. In this manner, a relatively large target portion C can be exposed, without having to compromise on resolution. In scan mode, the maximum size of the exposure field may limit the width (in the non-scanning direction) of the target portion in a single dynamic exposure, whereas the length of the scanning motion may determine the height (in the scanning direction) of the target portion;

[00038] 3. In another mode, the mask table MT is kept essentially stationary holding a programmable patterning structure, and the substrate table WT is moved or scanned

while a pattern imparted to the projection beam is projected onto a target portion C. In this mode, generally a pulsed radiation source is employed and the programmable patterning structure is updated as required after each movement of the substrate table WT or in between successive radiation pulses during a scan. This mode of operation can be readily applied to maskless lithography that utilizes programmable patterning structure, such as a programmable mirror array of a type as referred to above.

[00039] Combinations and/or variations on the above-described modes of use or entirely different modes of use may also be employed.

[00040] The optical system of the lithographic apparatus may be very important for the final quality of products produced by the lithographic apparatus. Therefore, it may be important to measure the characteristics of the optical system, and possibly to adjust one or more elements of the optical system (such as the projection lens PL), from time to time. In the conventional manner, such measurement may be performed by partial disassembly of the lithographic apparatus and installation of special test equipment in place of the wafer W (or wafer stage WT).

[00041] In Fig. 2, a top view is shown of a sensor arrangement 10 according to an embodiment of the present invention. The sensor arrangement 10 comprises a semiconductor wafer 1, on which a number of elements are formed as integrated circuits on the wafer 1.

[00042] The elements comprise a number of sensors 2 (or sensor arrays), processing electronics (e.g. a processing circuit, such as an array of logic elements configured to execute a series of operations) 4 receiving the output signals of the sensors 2, and a memory 6 connected to the processing circuit 4. The memory 6 may comprise a non-volatile part for storing operational instructions for the processing circuit 4, and a volatile or non-volatile part for storing measurement data. Furthermore, an input/output unit (e.g. an interface circuit) 8 is present which is connected to the processing circuit 4, and a power supply unit 9. The input/output unit 8 can transfer data from the sensor arrangement 10 to an external device, and the power supply unit 9 provides operating power to the elements on the sensor arrangement 10.

[00043] Furthermore, the wafer 1 may comprise alignment marks 5, which may be comparable to alignment marks in normal wafers W to be processed and may be used to align the wafer 1 in the lithographic apparatus.

[00044] In an alternative form, it is possible to have a number of separate sensor arrangements 10 integrated on the wafer (i.e. a combination of sensors 2 with one or more of processing electronics 4, memory 6, I/O unit 8 and power supply unit 9). Each of the sensor arrangements 10 may then be arranged to measure a specific characteristic of the lithographic apparatus (see below).

[00045] In at least some implementations, the sensor arrangement 10 can be used to measure optical properties of the lithographic apparatus without the necessity to disassemble the lithographic apparatus. For example, the sensor arrangement 10 may be configured to be transportable inside the lithographic apparatus as a normal wafer W.

[00046] The sensors 2 can be of various types and/or measurement principles. For calibration and optimization purposes, it may be desirable to evaluate the spatial image as formed by the illuminating system IL and projection lens PL frequently. For such an application, the sensors 2 can be arranged to monitor the spatial intensity distribution at the wafer position in three dimensions. The sensors 2 can also be used to measure the position of special marks which are scarcely present on production masks MA and abundantly present on special purpose masks MA. Also, the sensors 2 can be arranged to measure the shape of the point-spread function when imaging small mask features. Such information can be processed to obtain detailed information on the lithographic apparatus, such as lens and condenser aberrations.

[00047] In a specific embodiment, the sensors 2 comprise diode arrays integrally formed as integrated circuits in the wafer 1. It may be desirable to characterize the diode arrays (initially and/or periodically), e.g. in order to account for factors that may include differences in response among the array elements, changes in response over time, device aging and/or contamination, etc.

[00048] Alternatively, also the light intensity over the field (e.g. illumination uniformity at wafer level) can be measured too (e.g. to provide a spot sensor functionality). Also, stray light effect can be measured.

[00049] The sensors 2 may be connected to processing electronics 4. In the embodiment shown, all sensors 2 on the wafer 1 are connected to a single integrated circuit for processing of the sensor signals. Alternatively, part of the processing electronics 4 may be located directly adjacent to the sensor 2 on the wafer. The processing electronics 4 may perform signal pre-processing (such as integration and digitization), but can also perform more complex computations, e.g. based on the signals of more than one (possibly all) sensors 2 on the wafer 1.

[00050] Connections to external devices for further processing of the sensor arrangement signal and for power supply of the sensor arrangement 10 can be made by physical connections, e.g. using a special type of removable connector on the wafer stage WT. However, such a solution may be very cumbersome and could require additional equipment inside the lithographic apparatus. Therefore, in an alternative embodiment, the sensor arrangement 10 on the wafer 1 is provided in combination with a chuck, the chuck being the part of the wafer stage WT on which the wafer is held. The combination of sensor arrangement 10 and chuck can be positioned temporarily as a replacement chuck in the wafer stage WT during measurement. The combination of chuck and sensor arrangement 10 can be a portable unit, which can be connected to the internal Ethernet or other data network of the lithography apparatus, allowing it to be controlled by the lithographic apparatus software. The replacement chuck may provide all, or only a part (e.g. positioning in fewer than six degrees of freedom), of the functionality of the chuck which it replaces.

[00051] However, this first alternative may still require temporary removal of certain parts of the lithography apparatus. Therefore, in a further alternative embodiment, both the I/O unit 8 and the power supply unit 9 operate in a wireless manner.

[00052] The operating power necessary to operate the sensor arrangement 10 may be supplied using e.g. RF power. In such a case, the power supply unit 9 may comprise an antenna (which may be attached to or integrated in the wafer 1) and a circuit to

convert the received RF power into DC or AC power as required. In a special embodiment, the power supply unit 9 is arranged to receive RF power at different frequencies. Depending on the frequency, a specific sensor arrangement 10 (when multiple sensor arrangements 10 are present on a wafer 1) is supplied with operating power.

[00053] Also, the I/O unit 8 may operate using RF signal exchange. In this case, the I/O unit 8 may comprise an antenna attached to or integrated in the wafer 1 (which may be separate from or the same as an antenna of the power supply unit 9, if provided). The processing electronics 4 may be arranged to co-operate with the I/O unit 8 to allow data exchange to an external device. E.g., the external device can request a predetermined set of data stored in the memory 6, and/or the external device can upload amended operating instructions for the processing electronics 4 to be stored in the memory 6. When multiple sensor arrangements 10 are present on the wafer 1, a multiplexing technique (e.g. frequency-division multiplexing) may be used to address a specific one of the I/O units 8.

[00054] It is conceivable that other wireless techniques may be used by the I/O unit 8 and/or power supply unit 9, e.g. using light. Light (electromagnetic radiation) can be used to transfer energy or data. It is conceivable, for example, to integrate solar cells or other photo-voltaic cells in the wafer 1 to provide power. Various addressing techniques, known as such, may be used.

[00055] External elements for supplying power to and/or for providing interfacing with the sensor arrangement 10 may be positioned, for example, inside the lithographic apparatus (e.g. close to a wafer table WT, one example of which is shown in Fig. 1). For example, the test arrangement 10 may be connected to a data network of the lithographic apparatus. Such a connection may allow fully automatic testing and adjustment of the optical system of the lithographic apparatus. Alternatively, these elements may be provided outside of the lithographic apparatus. A potential advantage of the latter arrangement is that a portable test set may be composed, comprising a wafer 1 with the sensor arrangement 10 and external equipment for providing power and data exchange. Without a need to add further equipment to the lithographic apparatus, such a set may thus save cost.

[00056] As an alternative, it is possible to store the measurement data (raw data or processed data) in the wafer memory 6, and retrieve this data off-line, i.e. outside of the lithographic apparatus.

[00057] In Fig. 3, an example is shown of a possible test scenario including an embodiment of the present invention. It is noted that the embodiment of the sensor 2 as described below may also be used as such in a different sensor arrangement. To test optical properties of e.g. a projection lens system PL of a lithographic apparatus, the sensor arrangement 10 is positioned at the normal wafer position. A suitable test mask is positioned on the mask table MT. In Fig. 3, this is shown in a simplified view, in which the test mask is denoted by reference numeral 13, and the projection lens system PL by reference numeral 14. The sensor 2 comprises a photodiode 11 and a detector mask 12, which may both be integrated in the wafer 1.

[00058] Both the test mask 13 and the detector mask 12 comprise N x N regularly spaced transparent holes 15, which each have a diameter that is small compared to λ NA (λ being the wave length of the projected light, and NA being the numerical aperture of the projection lens 14). The pitch of the holes 15 is large compared to the resolution of the projection lens 14. In this arrangement, essentially the point-spread function of the lens can be observed by the sensor 2, with the intensity increased by a factor which is equal to the number of holes N^2 . The wafer 1 can be scanned in three dimensions, thus allowing recording the aerial image or point-spread function. A mathematical procedure to determine distortion, focal plane and other high-order lens aberrations from the observed point spread function is known. The described approach has the advantage that the measurement conditions can be made to correspond to the normal exposure conditions of a wafer W being processed in the lithographic apparatus.

[00059] The combination of test mask 13 and sensor 2 can also be provided with other optical features, in order to be able to measure various types of aberrations. The array of δ -type of objects (holes 15) is suitable for measuring the projection lens aberration. A Fresnel zone lens as test mask 13 allows detecting condenser lens aberrations. Large squares on the test mask 13 allows measurement of stray light characteristics. Regular device patterns (normal production masks MA) allow

measurement of pattern fidelity and to optimize illumination conditions. A brick wall structure on the test mask 13 allows measuring other aberrations.

[00060] The sensor 2 described with reference to Fig. 3 can be used as a single sensor 2 in a sensor arrangement 10 according to an embodiment of the present invention. However, it is also possible to combine a number of these sensors in a sensor array. Also, sensors or sensor arrays 2 can be provided spread out on the surface of the wafer 1, possibly to allow probing of the entire image field of the lithographic apparatus in a single step. Such an arrangement may be used to quickly perform uniformity measurements across the entire image field. Also, it is possible to provide sensors 2 in combination with patterns on the test mask 13 as described above, for example to allow measurement and detection of various types of aberrations in a single-step test.

[00061] In a further embodiment, the sensor arrangement 10 is provided on a substrate 1 with a different form, allowing it to be positioned at the position of the mask MA in the mask table MT. Such an arrangement may be used to allow specific measurements of the optical system of the lithographic apparatus up to the mask table MT (e.g. an illumination system IL as described above with reference to Fig. 1).

[00062] The invention has been explained using an exemplary embodiment specifically directed at a refractive optics lithographic apparatus. However, the invention can also be used in other types of lithographic apparatus, such as reflective optics lithographic apparatus. Furthermore, the present invention can be used in all types of lithographic apparatus, such as deep UV, 193 nm, 157 nm or EUV types.

[00063] A sensor arrangement according to an embodiment of the invention comprises a substrate, e.g. a semiconductor substrate such as a silicon substrate, in which the substrate comprises at least one sensor element, processing electronics connected to the at least one sensor element, an input/output unit connected to the processing electronics, and a power supply unit for supplying operating power to the sensor arrangement, in which the at least one sensor element is provided as an integrated circuit in the substrate.

[00064] Such a sensor arrangement can be used in the device as a normal substrate to be processed. Therefore, measurement and characterization of the optical properties

can be executed without further disassembly and assembly work on the device. As the at least one sensor element is integrated in the substrate, the optical properties of the device are measured at the right position. The at least one sensor element can be a photo-sensitive semiconductor element, such as a photo cell, photo diode, photo transistor or even a photo-voltaic cell.

[00065] In a further embodiment, also the processing electronics, the input/output unit and/or the power supply unit are provided as integrated circuits or other structures in the substrate or attached thereto (e.g. on or above the surface). This provides a sensor arrangement which can be handled as a usual substrate or wafer. Also, multiple sensor arrangements can be integrated on a single wafer. Using such an embodiment, a single test wafer may be provided which can be used to measure various optical properties of the device, using a specific one of the multiple sensor arrangements. Also, measurements can be executed involving the complete substrate surface, which allows single-step uniformity measurements.

[00066] The processing electronics are in a further embodiment connected to a memory (e.g. volatile and/or non-volatile) configured to store software code and/or data. The software code is used to program the processing electronics and can be changed to make the sensor arrangement suited for specific types of measurements.

[00067] In a further embodiment, the input/output unit is arranged to exchange data with an external device using wireless communication techniques. The wireless communication technique may be based on RF techniques or using light communication. This allows the sensor arrangement to be used as a stand-alone unit, which can be handled by the device like a normal substrate to be processed.

[00068] Also, the power supply unit may be arranged to convert wireless energy into a supply voltage for the sensor arrangement, such as a transponder type of converter. The power supply unit may be further arranged to convert wireless energy having a predetermined frequency into a supply voltage for a predetermined part of the sensor arrangement. The predetermined part may e.g. be a combination of one or more sensor elements, processing electronics and memory on a specific part of the substrate or having a specific type of test arrangement. In this manner, the power is only

delivered and consumed in that part, which may result in less power consumption and/or less formation of hot spots in the substrate.

[00069] In a further embodiment, the sensor arrangement further comprises a chuck on which the sensor arrangement is mounted, the chuck being mountable to the wafer stage of a lithographic apparatus. The chuck may comprise interface means for connecting the sensor arrangement to a data network in the lithographic apparatus. With such an embodiment, it may be possible to use the sensor arrangement as a portable unit and to bring it to a device to be tested, such that only a small part has to be installed in the lithographic apparatus to perform the measurements.

[00070] A lithographic apparatus according to one embodiment of the invention includes an illumination system for providing a beam of radiation; a support structure for supporting patterning structure, the patterning structure serving to impart the beam with a pattern in its cross-section; a substrate table for holding a substrate; a projection system for projecting the patterned beam onto a target portion of the substrate; and a sensor arrangement as described herein, in which the at least one sensor element and processing electronics are arranged to measure the aberration of one or more of the optical systems of the lithographic apparatus.

[00071] The sensor arrangement may be used to test and measure the optical properties of the lithographic apparatus, such as the illumination system and the projection system. These systems may use both refractive and reflective optics. Specific combinations of sensor elements and test patterning means or test masks may be used to test specific types of optical properties.

[00072] A method for measuring properties, such as optical properties, of a device arranged to process substrates, includes entering a sensor arrangement as described herein and positioning the sensor arrangement in a measurement position; executing measurements using the sensor arrangement; and removing the sensor arrangement from the device.

[00073] Using an embodiment of the present sensor arrangement, in which all sensor arrangement elements are integrated in a single substrate, it is possible to have the sensor arrangement transported through the device, such as a lithographic apparatus,

just as a normal substrate to be processed. Such an arrangement ma allows quick and more frequent testing of the (e.g. optical) properties of the device, without the necessity to dissassemble and/or stop operating the device.

[00074] Whilst specific embodiments of the invention have been described above, it will be appreciated that the invention as claimed may be practiced otherwise than as described. It is explicitly noted that the description of these embodiments is not intended to limit the invention as claimed.

CLAIMS

1. A sensor arrangement comprising a substrate, said sensor arrangement having:

at least one sensor element provided as an integrated circuit in the substrate; a processing circuit connected to the at least one sensor element; an input/output interface connected to the processing circuit; and a power supply unit configured to supply operating power to at least one other component of the sensor arrangement.

- 2. The sensor arrangement according to claim 1, wherein the sensor is an optical sensor.
- 3. The sensor arrangement according to claim 1, wherein the substrate is configured to fit into a wafer chuck of a lithographic apparatus.
- 4. The sensor arrangement according to claim 1, wherein at least one of the processing circuit, the input/output interface, and the power supply unit is provided as an integrated circuit in the substrate.
- 5. The sensor arrangement according to claim 1, wherein the processing circuit is connected to a memory configured to store at least one among software code and data.
- 6. The sensor arrangement according to claim 1, wherein the input/output interface is arranged to exchange data with an external device using a wireless communication technique.
- 7. The sensor arrangement according to claim 1, wherein the power supply unit is arranged to convert a wireless signal into a supply voltage for at least one other component of the sensor arrangement.
- 8. The sensor arrangement according to claim 7, wherein the power supply unit is arranged to convert wireless energy having a first predetermined

frequency into a supply voltage for a first part of the sensor arrangement and to convert wireless energy having a second predetermined frequency into a supply voltage for a second part of the sensor arrangement different from the first part.

- 9. The sensor arrangement according to claim 1, wherein the sensor arrangement further comprises a chuck on which the sensor arrangement is disposed, the chuck being mountable to a wafer stage of a lithographic apparatus.
- 10. The sensor arrangement according to claim 9, wherein the chuck comprises an interface configured to connect the sensor arrangement to a data network of the lithographic apparatus.
 - 11. A lithographic apparatus comprising:

a sensor arrangement comprising a substrate, said sensor arrangement having: at least one sensor element provided as an integrated circuit in the substrate;

a processing circuit connected to the at least one sensor element; an input/output interface connected to the processing circuit; and a power supply unit configured to supply operating power to at least one other component of the sensor arrangement, and

a projection system configured to project a patterned beam of radiation onto a target portion of the substrate;

wherein the sensor arrangement is arranged to measure an aberration of the projection system.

- 12. The lithographic apparatus according to claim 11, wherein the substrate is configured to fit into a wafer chuck of the lithographic apparatus.
- 13. The lithographic apparatus according to claim 11, wherein at least one of the processing circuit, the input/output interface, and the power supply unit is provided as an integrated circuit in the substrate.

- 14. The lithographic apparatus according to claim 11, wherein the processing circuit is connected to a memory configured to store at least one among software code and data.
- 15. The lithographic apparatus according to claim 11, wherein the input/output interface is arranged to exchange data with an external device using a wireless communication technique.
- 16. The lithographic apparatus according to claim 11, wherein the power supply unit is arranged to convert a wireless signal into a supply voltage for at least one other component of the sensor arrangement.
- 17. The lithographic apparatus according to claim 11, wherein the lithographic apparatus further comprises a chuck disposed on a wafer stage of the lithographic apparatus and on which the sensor arrangement is disposed.
- 18. The lithographic apparatus according to claim 17, wherein the chuck comprises an interface configured to connect the sensor arrangement to a data network of the lithographic apparatus.
- 19. A method for measuring properties, such as optical properties, of a device arranged to process substrates, comprising

entering a sensor arrangement in the device and positioning the sensor arrangement in a measurement position;

executing measurements using the sensor arrangement; and removing the sensor arrangement from the device,

wherein the sensor arrangement comprises a substrate, said sensor arrangement having:

at least one sensor element provided as an integrated circuit in the substrate;

a processing circuit connected to the at least one sensor element; an input/output interface connected to the processing circuit; and a power supply unit configured to supply operating power to at least one other component of the sensor arrangement.


20. The method according to claim 19, wherein the substrate is configured to fit into a wafer chuck of the device.

SENSOR FOR LITHOGRAPHIC APPARATUS AND METHOD OF OBTAINING MEASUREMENTS OF LITHOGRAPHIC APPARATUS

ABSTRACT

A sensor arrangement may be used to measure properties, such as optical properties, of a device arranged to process substrates. The sensor arrangement includes a substrate having the following: at least one sensor element, processing electronics connected to the at least one sensor element, an input/output unit connected to the processing electronics, and a power supply unit to supply operating power to the sensor arrangement. The at least one sensor element and possibly the processing electronics, the input/output unit, and/or the power supply unit may be provided as one or more integrated circuits or other structures in the substrate.

Fig 1






Fig 3

